

Air/Liquid Thermocouple

Air/Liquid Thermocouple

High performance manifold sensor with mini-plug

- Type "K" .062" Ungrounded sensor O.D. Manifold Probe with mini-plug.
- 1/8" NPT stainless fitting with strain relief spring.
- Fast response times (600+ milliseconds) and consistent stable readings.
- Uses durable Teflon™ wiring with stainless steel overbraid.
- Capable of withstanding extreme vibration and temperatures. Blaze probes are made with 316 SST sheathing able to withstand temperatures of 1650° +F.
- Racetrack tested, approved, and used by professional race teams.
- Hand made in the U.S.A

Sensor Type	Type K (Chromel / Alumel)
Temperature Range	32°F ~ 1650°F
Sensor O.D.	.062" Diameter
Junction Type	Ungrounded
Bend	N/A
"A" Dimensions	.300"
"AA" Dimension	N/A
Wire	Teflon™ (with SST Overbraid)
Wire Lengths	12"
Hardware	1/8" NPT Weld-In Fitting
Terminal	Mini-Plug

All products manufactured by FUELTECH are warranted to be free from defects in material and workmanship for three months following the date of original purchase.





FuelTech

455 Willbanks Dr.

Ball Ground, GA 30107

678-493-3835

www.fueltech.net